



ISO 4762 EN

d	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18
P	0,5	0,7	0,8	1	1,25	1,5	1,75	2	2	2,5
b	18	20	22	24	28	32	36	40	44	48
dk (max)	5,5	7	8,5	10	13	16	18	21	24	27
k (max)	3	4	5	6	8	10	12	14	16	18
s	2,5	3	4	5	6	8	10	12	14	14
L	(5-30)	(6-40)	(9-50)	(10-60)	(12-80)	(16-100)	(20-120)	(25-140)	(25-160)	(30-160)
d	M20	M22	M24	M27	M30	M33	M36	M42	M48	M56
P	2,5	2,5	3	3	3,5	3,5	4	4,5	5	6,5
b	52	56	60	66	72	78	84	96	108	124
dk (max)	30	33	36	40	45	50	54	63	72	84
k (max)	20	22	24	27	30	33	36	42	48	56
s	17	17	19	19	22	24	27	32	36	41
L	(30-200)	(35-220)	(40-260)	(45-260)	(45-300)	(50-300)	(55-300)	(60-300)	(70-300)	(160-300)

4.6 4.8 5.6 5.8 6.8 8.8 ● 10.9 ● 12.9 ● A2 ● A4 ●

